


	INTAKE	EXHAUST
ADVERTISED DURATION	264°	264°
ACTUAL CAM LIFT (in/mm)	.344" / 8.74mm	.344" / 8.74mm
ROCKER ARM RATIO	1:1	1:1
CENTERLINE	106°	114°
LOBE SEPERATION	110°	
DURATION AT 0.050" CAM	216°	216°
DURATION AT 0.050" VALVE	216°	216°
VALVE CLEARANCE	.008" / .203mm COLD	.010" / .254mm COLD
RECOMMENDED SPRING KIT	BC0350 (Single) or BC0350-2 (Single Shim Over Bucket)	

CAMSHAFT TIMING AT 0.050" VALVE LIFT	OPEN	CLOSES
	INTAKE	2° BTDC
EXHAUST	42° BBDC	6° BTDC



## NOTES

BUCKET DIAMETER: 1.200"

Warning: BC0350 spring/retainer kit for use on shim under bucket only. BC0350-2 spring/retainer kit for use on shim over bucket and shimless bucket only.

BC does not recommend using synthetic oil during break-in or operation. Follow OEM manufacturer's torque sequence and specifications. Use liberal amount of aftermarket engine assembly lube during installation. Check follower or bucket surfaces for abnormal wear and/or scuffing. On initial start-up and break-in run engine at 1500-2500 rpm for 20 minutes. **Camshafts damaged by improper installation, excessive spring pressure or retainers contacting valve guides or seals are void from warranty. Not legal for sale or use on emission controlled motor vehicles.**

